

MOISTURE GUARD®

ICE & RAIN UNDERLAYMENT

MANUFACTURED IN JOPLIN, MO

PRODUCT DATA

DESCRIPTION

Information included in this product data sheet was current at time of printing.

To obtain a copy of the most current version of this product data sheet, visit us online at tamko.com or call us at 800-641-4691.

MOISTURE GUARD® underlayment is a self-adhering, fiberglass and modified bitumen underlayment with a mineral surfacing, a removable release film on the adhesive side and removable selvage release tape.

- Self-adhering SBS modified asphalt
- Mineral surfacing
- Fiberglass mat
- Split treated release film
- Selvage release tape
- 5-Year Limited Warranty and Arbitration Agreement**

USES: For use as a self-adhering underlayment prior to installation of the final roof system and as a secondary layer used in areas susceptible to wind blown rain and ice damming. Moisture Guard is used on roof decks, along rake and eave edges, valleys and ridges, and around chimneys, dormers, vents and skylights. Moisture Guard is used under most types of roofing, including tile, wood shake, asphalt, slate or composite shingles. It is not recommended for use under metal roofing.*

BUILDING PRODUCTS BEGIN TO AGE AS SOON AS THEY ARE EXPOSED TO NATURE. BUILDINGS EXPERIENCE AGING FACTORS DIFFERENTLY, SO IT IS DIFFICULT TO PREDICT HOW LONG BUILDING PRODUCTS WILL LAST. TAMKO PROVIDES A LIMITED WARRANTY FOR MANY PRODUCTS, THAT INCLUDES A BINDING ARBITRATION CLAUSE AND OTHER TERMS AND CONDITIONS WHICH ARE INCORPORATED HEREIN BY REFERENCE. YOU MAY OBTAIN A COPY OF THE LIMITED WARRANTY AT TAMKO.COM OR BY CALLING 1-800-641-4691.

* Use TAMKO TW Metal & Tile Underlayment or TW Underlayment for metal roofing applications.

** See complete TAMKO Asphalt Underlayments Limited Warranty and Arbitration Agreement on tamko.com for details.

TECHNICAL INFORMATION

UL Prepared Roofing Accessory

UL Classified in accordance with: ASTM D1970

Florida Building Code Approved: FL12328

Miami-Dade County Product Control Approved

LIMITATIONS

- Underlayment must not be applied to wet or frosty surfaces.
- Underlayment should not be applied to unclean or contaminated surfaces.
- Underlayment must not come into contact with products containing coal-tar pitch.
- Best applied at temperatures of 40 °F and higher.
- Once applied, underlayment must not be left exposed beyond 90 days.

PRODUCT DATA

Roll Size†	0.87 Sales Square Roll	1.74 Sales Square Roll
Roll Dimensions†	36" × 32'3"	36" × 64'6"
Roll Coverage††	87.34 sq. ft. (± 1.52 sq. ft.)	174.69 sq. ft. (±1.52 sq. ft.)
Roll Contains	96.75 sq. ft. (± 1.68 sq. ft.)	193.5 sq. ft. (±1.68 sq. ft.)
Thickness	55 mils	55 mils
Rolls Per Pallet	42	25
Pallet Size	37" × 47"	37" × 47"

† Subject to manufacturing variation

†† When applied according to application instructions



IMPORTANT SAFETY INFORMATION: Do not install until all appropriate safety precautions have been read and understood. The TAMKO Safety Data Sheet (SDS) is available at tamko.com/sds. Always use appropriate fall protection equipment and wear appropriate personal protective equipment (PPE) when working with this product. Moisture, frost, debris or other material will decrease the traction and can cause slippery conditions when walking on the product. **Applicator safety is of utmost importance.**

WARNING: Use of this product in an assembly that includes polyurethane foam insulation (including without limitation an application directly to the underside of a roof deck or within a wall assembly) may cause premature degradation or failure of this product. We continue to evaluate compatibility of polyurethane foams with our asphalt building products. Chemical incompatibility, off-gassing after application and excess heat during and after application of polyurethane foams may affect the performance of asphalt and modified asphalt building products and metal fasteners used with those products.

P.O. Box 97
Galena, KS 66739-0097
800-641-4691
tamko.com