

TAMKO® TWP-LV1 ADHESIVE PRIMER

WATERPROOFING PRIMER

PRODUCT DATA

DESCRIPTION

Information included in this product data sheet was current at time of printing.

To obtain a copy of the most current version of this product data sheet, visit us online at tamko.com or call us at 800-641-4691.

TAMKO® TWP-LV1 ADHESIVE PRIMER is a quick drying, rubberized, solvent based, low VOC adhesive primer formulated for use with self-adhered membranes.

- Available in 5 gallon pails
- Applied with a long nap roller or brush
- Features a red tint to make it easier to identify areas that have been primed
- 5-Year Limited Warranty and Arbitration Agreement

USES: To promote a powerful bond to asphalt, metal surfaces, OSB, plywood, DensGlass®, concrete, masonry block, or exterior gypsum sheathing.

WATERPROOFING PRODUCTS BEGIN TO AGE AS SOON AS THEY ARE EXPOSED TO NATURE. BUILDINGS EXPERIENCE AGING FACTORS DIFFERENTLY, SO IT IS DIFFICULT TO PREDICT HOW LONG WATERPROOFING PRODUCTS WILL LAST. THAT'S WHY TAMKO PROVIDES A LIMITED WARRANTY THAT INCLUDES A BINDING ARBITRATION CLAUSE AND OTHER TERMS AND CONDITIONS WHICH ARE INCORPORATED HEREIN BY REFERENCE. YOU MAY OBTAIN A COPY OF THE LIMITED WARRANTY AT TAMKO.COM OR BY CALLING 1-800-641-4691.

APPLICATION

Apply with a long nap roller or brush with an estimated coverage of 250 to 300 square feet per gallon. Allow to cure until the surface is tacky but will not transfer when touched. Do not thin with organic solvents.

LIMITATIONS

- TWP-LV1 Adhesive Primer must not be used on or come into contact with EPS/XPS or ICF surfaces.

TYPICAL PHYSICAL PROPERTIES

Solid Contents	46.6% by weight
Tack Free Time	10 min. @ 75 °F
VOC	Less than 250 grams/liter
Flash Point	-4 °F



P.O. Box 1404
Joplin, MO 64802-1404
800-641-4691
tamko.com



IMPORTANT SAFETY INFORMATION: Do not install until all appropriate safety precautions have been read and understood. [The TAMKO Safety Data Sheet \(SDS\) is available at tamko.com/sds](http://tamko.com/sds). Always use appropriate fall protection equipment and wear appropriate personal protective equipment (PPE) when working with this product. Moisture, frost, debris or other material will decrease the traction and can cause slippery conditions when walking on the product. **Applicator safety is of utmost importance.**